

# STRUB Vulcomp HC VDL

Semi-synthetic compressor oil for use in screw and four-cell compressors.

## Description

The ashless long-life compressor oil with synergistically interacting, latest additives enables sticky, brown oxidation residues to become a thing of the past. STRUB HC VDL line easily lasts for 4000 operating hours, even at slightly increased oil temperatures of 70°C - 90°C.

## Application

For all screw compressors where an extended oil change interval is specified.

## Features and advantages

- extended oil change intervals > 4000 Bh
- excellent aging resistance
- low evaporation
- very good demulsifying capacity
- avoidance of coke residues
- excellent air cutting properties, lowest foam formation
- sealing compatibility
- excellent corrosion protection
- ash-free with unique antioxidant technology
- maximum performance
- optimal run-out behavior

## Specifications

DIN 51506 VDL, VBL, VCL
DIN 51524 Teil 2 HLP
ISO/DP 6521, 6743-3A, 3B

## Technical data

ISO		32	46	68	100
Art. No.		31065	31066	31067	33149
Color		yellow	yellow	yellow	yellow
Density at 20°C	g/cm <sup>3</sup>	0.840	0.844	0.845	0.851
Viscosity at 40°C	mm <sup>2</sup> /s	32	46.4	68	100
Viscosity at 100°C	mm <sup>2</sup> /s	5.9	7.6	10.2	14.1
Viscosity index (VI)		130	130	136	144
Pour point	°C	- 21	- 18	- 15	- 18
Flash point	°C	220	258	260	260
Corrosion protection/steel DIN 51585		0-A	0-A	0-A	0-A

## Transport

ADR/SDR No dangerous goods

## Disposal

LVA VeVA / EAK: 13 02 08

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.