

STRUB Vulcomp VDL N 46 & 68

Special compressor oil

Description

STRUB Vulcomp VDL N 46 and 68 are special compressor oils.

Application

For all screw compressors (ISO VG 46 and ISO VG 68) where an extended oil change interval is specified.

Features and advantages

- extended oil change intervals
- excellent aging resistance
- low evaporation and no residues
- excellent fast phase separation
- minimal formation of coke residue
- excellent sealing compatibility
- excellent corrosion protection
- wide temperature application range

Specifications

DIN 51506 VDL ISO/DP 6521, 6743-3A, 3B

Technical data

ISO		46	68
Art. No.		30433	30019
Color		blue-greenish	blue-greenish
Density at 20°C	g/cm ³	0.860	0.870
Viscosity at 40°C	mm ² /s	46	68
Viscosity at 100°C	mm ² /s	7.2	9
Corrosion test ASTM 665A		pass	pass
Pour point	°C	-35	-30
Flash point	°C	230	240

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 13 02 08

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.