

STRUB Vulcan Diamant 60/CL liquid

High performance
 Multipurpose lubricant

Art.-No. 31344

Description

All-round lubricant for joints, bolts, chains, hinges, etc.
 The product also acts as an additive in lubricating oils to prevent galling/settling of metal couples.

Application

Cutting, sawing, threading, tapping, punching, bending, spinning, forming in steel and highest alloyed metals, including chrome steel. Metalworking, industrial maintenance, wood, paper, plastics, automotive, aircraft industries and shipyards. Almost unlimited lubricant use.

Features and advantages

- High pressure (EP)
- Anti-wear (AW)
- Water displacing (DW)
- excellent creep capillary action
- ageing and heat stable (~ 250°C active ingredient)
- long-term lubrication

Technical data

Color		greenish
Shape		liquid
Density 20°C	gr/ml	0,896
Viscosity at 40°C	mm ² /s	5.4
Viscosity at 100°C	mm ² /s	8.4
Viscosity index		130
Temperature application	°C	-30 - 250

Transport

ADR/SDR UN 1950, Klasse 2, 5F

Disposal

LVA VeVA / EAK: 12 01 06

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.