

STRUB Food Adhesive Lube PTFE H1

Adhesive lubricant with PTFE



Art.-No. 32525

Description

Light-colored, very adhesive, fully synthetic high-performance lubricating oil with PTFE.

Application

For the lubrication of highly loaded machine elements, even under the influence of water. It is ideal for guides, chains, joints, fittings, hinges, locks, rolling and sliding bearings in precision engineering, beverage industry, breweries and food industry.

Features and advantages

- complies with H1 legislation
- long operating hours - service life
- good resistance to oxidation and aging
- resistant to cold and hot water
- can also be used with acidic or alkaline cleaning and disinfecting agents
- application with brush, dipping, dripping oil etc.
- also available in 500 ml aerosol cans

Note

Shake well before use

Technical data

Color	light beige	
Viscosity	40°C / mm ² /s	100
Pour point	< - 40°C	
Flash point	° C	> 240
Solid lubricant		PTFE
Density	g/cm ³	0,85
Application temperature open	°C	-35°C – 200°C
Application temperature Spray	°C	-10°C – 150°C
VKA welding load	DIN51350-2	N 2,600
Friction coefficient	mm	0,7

Container

available as 500 ml spray or in a 5 lt canister

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 13 01 12

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.