

# STRUB Vulcomet Protection 8040 BF-DW

Solvent-based corrosion protection and dewatering fluid, VOC 82 %.

Art.-No. 30274

---

## Description

Rust protection with thin, fast-drying protective film that does not stick and has water-displacing properties.

## Application

Protection of small parts during the manufacturing processes - intermediate storage - protection of parts ready for shipment. After-treatment during burnishing. 8040 BF-DW gives a matt, gray-black surface. Additional rust protection for yellow-chromated parts in the HF and electrical industry: Prevents discoloration, surfaces remain dry, does not bind dust.

## Features and advantages

- does not emulsify
- forms a thin protective film resistant to hand perspiration
- works absolutely reliable
- is very economical
- can, if desired, be removed without residues with STRUB Monafix-T-Special aqueous alkaline cleaner (dilution 1:10 to 1:30), Tri-Perchloraethane
- Water that enters the bath immediately sinks in drops to the bottom of the tank, from where it can be drained off separately if necessary
- does not attack machine paints

## Technical data

Spec. wt. at 20°C	g/ml	0.795
Flash point g.d.	°C	47
Film thickness	µm	0.8 - 1
Yield	m <sup>2</sup> /l	190
Staining on steel + non-ferrous metals		none
Drying. / evaporation time	Minutes	30
Corrosion test ASTM D-1748		
Humidity /Cabinet Days pass		60
Protection time Indoor storage	months	6 - 8
Outdoor storage under roof		
Water displacement MIL-C-16173E		Pass

## Transport

ADR/SDR Class 3, F1, packing group III  
UN-Code 1993

## Disposal

LVA VeVA / EAK 14 06 03

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.