

STRUB Multi Duty Grease PAO 2 and 3

Synthetic grease without dropping point

Art.-No. 33152, 33280

Description

STRUB Multi Duty Grease PAO is a synthetic and infusible grease (without drop point). Careful production and addition of high quality additives make it a high quality, universal grease.

Application

Its high service temperature allows frictionless lubrication where greases with a lithium soap have no power. Fields of application: Construction, garages, cement industry, mills, foundries, chemical industry, textile and metallurgical industry, transportation, agriculture, etc.

Technical data

NLGI		2	3
Item no.		33152	33280
Color		beige	beige
Thickener		inorganic	inorganic
Work Penetration 25°C / 60 strokes		265-295	220-250
Base oil viscosity	mm ² /s	150	150
Drip Point	°C	none	none
Operating temperature	°C	-40°C to 200°C	-40°C to 200°C
Maximum temperature (short term)	°C	250°C	250°C

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 12 01 12

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.