

STRUB Paste S

Universal assembly paste

Art.-No. 30455

Description

Universal paste with a very high content of synergistically acting solid lubricants.

Application

Dry cleaned surfaces or bodies and apply using a lint-free cloth, brush or paintbrush.

Features and advantages

- protects against fretting corrosion, vibration corrosion and cold welding
- makes screwed connections easier to loosen and keeps threaded spindles, joints, bolts, sliding guides smooth-running
- excellent for slow-running bearings which are under heavy static load (surface pressure)
- prevents squeaking of leaf springs

Technical data

Designation according to DIN	MPF3R-20
Thickener	Bentonite
Color	gray-black
Density at 20°C	1.25 - 1.45 g/cm ³
Rest penetration	220 - 280 1/10 mm
NLGI	2-3
Drop point	none
Base oil viscosity	30cSt
Solid lubricant	MoS ₂ and others
Operating temperature	-20 to +450°C
VKA Welding force	>5000 N
VKA Almen-Wieland machine Basic load	>19'000 N

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 12 01 12

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.