

STRUB Vulcan Estamp CF 9670

Chlorine-free punching and fine blanking oil



Art.-No. 30246

Description

Mineral oil-based special oil with a synergistically highly effective combination of chlorine-free high-performance additives.

Application

For punching, fine blanking and embossing of aluminum, copper and other non-ferrous metal alloys with material thicknesses up to 10 mm. Punching and fine blanking of steel and high-alloy steels works up to material thicknesses of 3 mm.

Features and advantages

- oxidation stable
- low evaporation
- free from solvents, PCBs and other organochlorine compounds

Technical data

Color		brown
Density at 20°C	g/ml	0.850
Viscosity at 40°C	mm ² /s	16
Flash point	°C	> 140
Pour point	°C	< - 25
Copper corrosion ASTM D130	3h (100°C)	1b

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK: 12 01 07

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.