

STRUB Universal Thinner

All purpose paint thinner

Art.-No. 30744

Description

Fast evaporating premium thinner with universal applications. Manufactured from pure high quality solvents. No regenerate is used or employed in its manufacture. The product covers cellulose synthetic resin thinners.

Application

STRUB Universal Thinner is a modern paint thinner for many paints, except for 2-component paints (note the pull-up). Synthetic resin paints must be tested for resistance beforehand!

Technical data

Density	0.848 g/cm ³
Flash point	<
Boiling point/ignition temperature	0°C/79°C/425°C/100
Solvent content	%

Transport

UN code 1993
ADR/SDR Class 3, F1, packing group III/MDG Code 3.3

Disposal

LVA VeVA / EAK: 14 06 03

Water protection

Must not enter drains, water courses or soil.

Levies

VOC subject to 100

Fire protection

The product contains flammable solvents. These can form ignitable mixtures with the air when evaporating. Secure container against electrostatic charge!

The information in this technical data sheet is based on general knowledge and possible applications. Strub + Co. AG is not liable for damage resulting from improper use of the products. The measurement and production tolerances customary in the industry apply to the characteristic data given. In general, no legal binding force can be derived from these data. Our products are subject to continuous further development. Therefore, Strub + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.