

STRUB Spindle Cooling Oil III

High-tech spindle cooling oil for high-speed spindles

Art.-No. 33132

Description

STRUB Spindle Cooling Oil III is a special and thin spindle cooling oil. It consists of a specific fraction mixture with specially developed synergistically acting additives. The excellent antioxidants and the special wear protection give the high-tech spindle fluid an optimal performance.

Application

STRUB Spindle Cooling Oil III has been specially developed for high speed spindles and is excellent for cooling for high performance machining centers.

Features and advantages

- cleanliness class 15/13/10 according to ISO 4406
- optimum corrosion protection
- good wear protection
- no foam formation
- balanced viscosity-temperature behavior
- excellent oxidation resistance
- low pour point

Technical data

Color		clear
Density at 20°C	g/cm ³	0.815
Viscosity at 40°C	mm ² /s	2.6
Flash point	°C	>100

Transport

ADR/SDR No dangerous goods

Disposal

LVA VeVA / EAK 12 01 07

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.