

STRUB Gear lubricant spray

Synthetic, excellent adhesive high-tech lubricant, VOC 365 g

Art.-No. 30700

Description

STRUB Gear Lubricant is a synthetic, high-tech lubricant with excellent adhesion. Suitable for lubrication points exposed to water, salt water or weather.

Application

STRUB gear lubricant spray is used for lubrication of gear rim, gear, racks, chains and pinions. In addition, the product is suitable for gears of sewage treatment plants, in the shipyard, cement, construction, steel and machinery industries.

Spray STRUB Gear Lubricant Spray on surfaces from a distance of approx. 10 - 30 cm. Do not use near open fire or sources of ignition.

Features and advantages

- the elastomeric lubricating film does not crack or break off as with standard bitumen-based products
- contains MoS₂ and graphite

Technical data

Operating temperature	°C	-20 - +80
-----------------------	----	-----------

Packing

12 x 500 ml aerosol cans with environmentally friendly propellant gas.

Transport

ADR/SDR 1950 / 2 / 2.1

Disposal

LVA VeVA / EAK 15 01 04 (metal packaging)

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.