

STRUB Universal-Oil-Spray MoS₂

VOC 142.00g

Art.-No. 30699

Description

Oil spray based on mineral oil and solid lubricant (MoS₂). Best emergency running properties.

Application

- lubricates chains, joints, bolts, hinges, cable pulls, leaf springs, etc.
- increases tool life and cutting accuracy of cutting tools
- protects against fretting corrosion
- improves workpiece quality during chipless forming of all metals
- can be used in various industries, such as mechanics, electronics, vehicles, etc.

Features and advantages

- prevents jerky sliding at creep speeds
- prevents the formation of fretting corrosion

Technical data

Color		dark gray
Density at 20°C	g/ml	~ 0.9
Viscosity at 40°C	mm ² /s	~ 150
Operating temperature		-20°C - 220°C

Transport

ADR/SDR UN 1950, Hazard label: 2.1, Class 2, 5F

Disposal

LVA VeVA / EAK 15 01 04 / 16 05 05

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.