

# STRUB Vulcolube X 1000

Cylinder oil

Art.-No. 30964

## Description

STRUB Vulcolube X 1000 is a pure, mineral oil based, high viscosity hot steam cylinder oil.

## Application

STRUB Vulcolube X 1000 is primarily suitable for lubricating the steam-wetted sliding parts on steam engines whose steam inlet temperature does not exceed 325°C.

Also suitable as a high-viscosity lubricating oil for lubrication points with through-feed lubrication.

## Features and advantages

- low tendency to residue formation
- excellent aging resistance
- very good water separation capacity/ condensate
- good wear protection

## Specifications

Hot steam cylinder oil according to DIN 51510

## Technical data

Density at 20°C	g/ml	DIN 51757/1	0.908
Visc. 40°C	mm <sup>2</sup> /s	ASTM D 445	1080
Visc. 100°C	mm <sup>2</sup> /s	D 445	55.6
Viscosity index		ISO 2909-81	100
Flash point COC	°C	ISO 2592-94	312
Pour point	°C	DIN ISO 3016	< - 3

## Transport

ADR/SDR No dangerous goods

## Disposal

LVA VeVA / EAK: 13 02 08

The information in this technical data sheet is based on general knowledge and application possibilities. STRUB + Co. AG is not liable for damage resulting from improper use of the products. The industry-standard measurement and production tolerances apply to the specified characteristic. Generally, no legal binding can be derived from these data. Our products are subject to continuous further development. Therefore, STRUB + Co. AG reserves the right to change all technical data in this data sheet at any time and without prior notice.